

1.	Foreword	1	Foreword
1.1	Connecting pipes world-wide	1	
2.	The principle	2	The principle
2.1	The STRAUB advantage	2	
2.2	Features and Benefits	3	
2.3	The Basic Concept	4	
2.4	Two types of STRAUB couplings	5	
2.5	Six products - One principle	6	
2.6	Selection guide	7	
2.7	Main range of applications	7	
3.	Properties	8	Properties
3.1	The progressive sealing effect	8	
3.2	The progressive anchoring effect	9	
3.3	Stress-free joining	10	
3.3.1	Anchoring	10	
3.3.2	Sealing	10	
3.4	Gaskets	11	
3.4.1	Quality and fields of application	11	
3.4.2	Temperature range	11	
3.4.3	Life expectancy	12	
3.5	Material specifications and corrosion-resistance	13	
3.5.1	Material specifications STRAUB pipe joint	13	
3.6	Space requirements	14	
3.7	Damping Properties	15	
3.7.1	Noise- and Vibration damping	15	
3.7.2	Balancing of pressure surges	17	
3.7.3	Shock resistance	17	
3.8	Installation times and dimension comparison	18	
3.9	Fitting / disassembly instructions STRAUB couplings	19	
3.10	Setting gap between pipe ends due to angular deflection α	21	
3.11	Minimum wall thickness for stainless steel and cooper nickel pipes	23	
3.12	STRAUB - Forces to avoid	24	
3.13	Products and Features	25	

4.	STRAUB-GRIP	26
4.1	STRAUB-GRIP-L	26
4.1.1	Metric Specification STRAUB-GRIP-L Ø 26.9 - 219.1 mm	27
4.1.2	Metric Specification STRAUB-GRIP-L Ø 193.0 - 609.6 mm	28
4.1.3	Imperial Specification STRAUB-GRIP-L Ø ¾ - 8 inch	29
4.1.4	Imperial Specification STRAUB-GRIP-L Ø 7.1 - 24 inch	30
4.2	STRAUB-METAL-GRIP	31
4.2.1	Metric Specification STRAUB-METAL-GRIP Ø 33.7 - 219.1 mm	32
4.2.2	Metric Specification STRAUB-METAL-GRIP Ø 244.5 - 609.6 mm	33
4.2.3	Imperial Specification STRAUB-METAL-GRIP Ø 1 - 8 inch	34
4.2.4	Imperial Specification STRAUB-METAL-GRIP Ø 9 - 24 inch	35
4.3	STRAUB-PLAST-/COMBI-GRIP	36
4.3.1	Metric Specification STRAUB-PLAST-/COMBI-GRIP Ø 40.0 - 160.0 mm	37
4.3.2	Imperial Specification STRAUB-PLAST-/COMBI-GRIP Ø 1¼ - 6 inch	38
4.4	Allowable pipe diameter tolerances	39
4.5	Max. allowable setting gap between pipe ends R	41
4.6	Angular deflection α	44
4.7	Axial movement Δl	46
4.8	Axial misalignment	47
4.9	Resistance against bending and torsion	47
4.10	STRAUB-METAL-GRIP on vertical piping	48
4.11	Special order couplings	49
4.11.1	Electrical conductivity of STRAUB-GRIP	49
4.11.2	Demagnetised couplings	49
4.11.3	Silicon-free couplings	49
5.	STRAUB-FLEX / STRAUB-REP	50
5.1	STRAUB-FLEX	50
5.1.1	Metric Specification STRAUB-FLEX 1L Ø 48.3 - 168.3 mm	51
5.1.2	Metric Specification STRAUB-FLEX 2 Ø 180.0 - 1600.0 mm	52
5.1.3	Metric Specification STRAUB-FLEX 3 Ø 558.8 - 2032.0 mm	53
5.1.4	Imperial Specification STRAUB-FLEX 1 Ø 1½ - 6 inch	54
5.1.5	Imperial Specification STRAUB-FLEX 2 Ø 7.1 - 63 inch	55
5.1.6	Imperial Specification STRAUB-FLEX 3 Ø 22 - 80 inch	56
5.2	STRAUB-REP	57
5.2.1	Metric Specification STRAUB-REP 1L Ø 48.3 - 168.3 mm	58
5.2.2	Metric Specification STRAUB-REP 2 Ø 180.0 - 1219.2 mm	59
5.2.3	Metric Specification STRAUB-REP 3 Ø 558.8 - 2032.0 mm	60
5.2.4	Imperial Specification STRAUB-REP 1L Ø 1½ - 6 inch	61

5.2.5	Imperial Specification STRAUB-REP 2 Ø 7.1 - 48 inch.....	62
5.2.6	Imperial Specification STRAUB-REP 3 Ø 22 - 48 inch.....	63
5.2.7	The STRAUB-REP concept	64
5.3	Allowable pipe diameter tolerances	66
5.4	Max. allowable setting gap between pipe ends R	67
5.5	Angular deflection α	69
5.6	Axial movement Δl	70
5.7	Axial misalignment	72
5.8	Resistance against bending and torsion	72
5.9	Special order couplings	73
5.9.1	Electrical conductivity of STRAUB-FLEX/-REP	73
5.9.2	Demagnetised couplings	74
5.9.3	Silicon-free couplings	74
6.	Accessories	75
6.1	Support rings STRAUB-PG	75
6.2	Strip inserts	76
6.2.1	Vacuum	77
6.3	Lock parts in stainless steel	78
6.4	REP installation tool	80
6.5	Torque wrench.....	80
7.	Approvals (extract)	81
7.1	Approvals Shipbuilding	82
7.2	Approvals Water	84
7.3	Approvals Gas	85
7.4	Approvals Mining	86
7.5	Approvals Fire Protection	87
7.6	Approvals Electricity	87
7.7	Special approvals	88